

# SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

## Ceramic PRO BASE

Creation date 30th January 2024  
Revision date Version 1.0

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

- 1.1. Product identifier** Ceramic PRO BASE  
Substance / mixture mixture  
UFI M820-30N8-000Y-18HF
- 1.2. Relevant identified uses of the substance or mixture and uses advised against**  
**Mixture's intended use**

#### Main intended use

PC-CLN-17.2 Exterior care products - all vehicle types

#### Mixture uses advised against

The product should not be used in ways other than those referred in Section 1.

### 1.3. Details of the supplier of the safety data sheet

#### Supplier

Name or trade name Magis Agata Nizio  
Address Mickiewicza 11, Dębno, 74-400  
Poland  
VAT Reg No PL5970003622  
Phone +48451013350  
E-mail ggg@gmail.com

#### Competent person responsible for the safety data sheet

Name Magis Agata Nizio  
E-mail ggg@gmail.com

### 1.4. Emergency telephone number

European emergency number: 112

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification of the mixture in accordance with Regulation (EC) No 1272/2008

The mixture is classified as dangerous.

Flam. Liq. 2, H225  
Asp. Tox. 1, H304  
Skin Irrit. 2, H315  
Eye Irrit. 2, H319  
STOT SE 3, H336

#### Most serious adverse physico-chemical effects

Highly flammable liquid and vapour.

#### Most serious adverse effects on human health and the environment

May be fatal if swallowed and enters airways. Causes serious eye irritation. Causes skin irritation. May cause respiratory irritation.

### 2.2. Label elements

#### Hazard pictogram



#### Signal word

Danger

#### Hazardous substances

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics  
Silicic acid (H<sub>4</sub>SiO<sub>4</sub>), tetraethyl ester, hydrolyzed  
tetraethyl silicate

#### Hazard statements

H225 Highly flammable liquid and vapour.

# SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

## Ceramic PRO BASE

Creation date 30th January 2024  
Revision date Version 1.0

H304 May be fatal if swallowed and enters airways.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.

### Precautionary statements

P102 Keep out of reach of children.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P280 Wear protective gloves.  
P301+P310 IF SWALLOWED: Immediately call a doctor.  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P331 Do NOT induce vomiting.  
P405 Store locked up.

### Supplemental information

5-<15 % aliphatic hydrocarbons

### Requirements for child-resistant fastenings and tactile warning of danger

Container must carry a tactile warning of danger. Container must be fitted with child-resistant fastening.

### 2.3. Other hazards

The mixture does not contain substances with endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605. Mixture does not contain any substance meet the criteria for PBT or vPvB in accordance with Annex XIII of Regulation (EC) No. 1907/2006 (REACH) as amended.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

#### Mixture contains these hazardous substances and substances with the highest permissible concentration in the working environment

Identification numbers	Substance name	Content in % weight	Classification according to Regulation (EC) No 1272/2008	Note
CAS: 64742-48-9 EC: 919-857-5 Registration number: 01-2119463258-33	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	20-30	Flam. Liq. 3, H226 Asp. Tox. 1, H304 STOT SE 3, H336 EUH066	
CAS: 68412-37-3 EC: 270-184-7	Silicic acid (H4SiO4), tetraethyl ester, hydrolyzed	5-10	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335	
Index: 014-005-00-0 CAS: 78-10-4 EC: 201-083-8	tetraethyl silicate	5-10	Flam. Liq. 3, H226 Eye Irrit. 2, H319 Acute Tox. 4, H332 STOT SE 3, H335	1
Index: 603-117-00-0 CAS: 67-63-0 EC: 200-661-7 Registration number: 01-2119457558-25	propan-2-ol	5-10	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336	

### Notes

1 A substance for which exposure limits are set.

Full text of all classifications and hazard statements is given in the section 16.

# SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

## Ceramic PRO BASE

Creation date	30th January 2024	Version	1.0
Revision date			

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

Do not perform artificial respiration without self-protection (e.g. a mask). Take care of your own safety. If any health problems are manifested or if in doubt, inform a doctor and show him information from this safety data sheet. If unconscious, put the person in the stabilized (recovery) position on his side with his head slightly bent backwards and make sure that airways are free; never induce vomiting. If the person vomits by himself, make sure that the vomit is not inhaled. In life threatening conditions first of all provide resuscitation of the affected person and ensure medical assistance. Respiratory arrest - provide artificial respiration immediately. Cardiac arrest - provide indirect cardiac massage immediately.

##### **If inhaled**

Terminate the exposure immediately; move the affected person to fresh air. Take care of your own safety, do not let the affected person walk! Beware of the contaminated clothes. Depending on the situation, call the medical rescue service and ensure medical treatment considering the frequent need of further observation for at least 24 hours.

##### **If on skin**

Remove contaminated clothes. Wash the affected area with plenty of water, lukewarm if possible. Soap, soap solution or shampoo should be used if there is no skin injury. Provide medical treatment if skin irritation persists. Rinse skin with water or shower.

##### **If in eyes**

Rinse eyes immediately with a flow of running water, open the eyelids (also using force if needed); remove contact lenses immediately if worn by the affected person. Rinsing should continue at least for 10 minutes. Provide medical treatment, specialized if possible.

##### **If swallowed**

If the affected person vomits, make sure to prevent inhalation of the vomit (as there is a danger of lung damage after inhalation of these liquids in the airways also in infinitesimal amount). Provide medical treatment considering the frequent need of further observation for at least 24 hours. Bring an original container with the label and the Safety Data Sheet of the given substance as appropriate.

#### 4.2. Most important symptoms and effects, both acute and delayed

##### **If inhaled**

Cough, headache. May cause respiratory irritation.

##### **If on skin**

Causes skin irritation.

##### **If in eyes**

Causes serious eye irritation.

##### **If swallowed**

Irritation, nausea.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

##### **Suitable extinguishing media**

Alcohol-resistant foam, carbon dioxide, powder, water spray jet, water mist.

##### **Unsuitable extinguishing media**

Water - full jet.

#### 5.2. Special hazards arising from the substance or mixture

In the event of fire, carbon monoxide, carbon dioxide and other toxic gases may arise. Inhalation of hazardous degradation (pyrolysis) products may cause serious health damage.

#### 5.3. Advice for firefighters

Self-Contained Breathing Apparatus (SCBA) with a chemical protection suit only where personal (close) contact is likely. Use a self-contained breathing apparatus and full-body protective clothing. Closed containers with the product near the fire should be cooled with water. Do not allow run-off of contaminated fire extinguishing material to enter drains or surface and ground water.

# SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

## Ceramic PRO BASE

Creation date 30th January 2024  
Revision date Version 1.0

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

Provide sufficient ventilation. Highly flammable liquid and vapour. Remove all ignition sources. Use personal protective equipment for work. Follow the instructions in the Sections 7 and 8. Do not inhale mist/vapours/spray. Prevent contact with skin and eyes.

#### 6.2. Environmental precautions

Prevent contamination of the soil and entering surface or ground water.

#### 6.3. Methods and material for containment and cleaning up

Spilled product should be covered with suitable (non-flammable) absorbing material (sand, diatomaceous earth, earth and other suitable absorption materials); to be contained in well closed containers and removed as per the Section 13. In the event of leakage of the substantial amount of the product, inform fire brigade and other competent bodies. After removal of the product, wash the contaminated site with plenty of water. Do not use solvents.

#### 6.4. Reference to other sections

See the Section 7, 8 and 13.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Prevent formation of gases and vapours in flammable or explosive concentrations and concentrations exceeding the occupational exposure limits. The product should be used only in the areas where it is not in contact with open fire and other ignition sources. Use non-sparking tools. Use of antistatic clothes and footwear is recommended. Do not inhale mist/vapours/spray. Prevent contact with skin and eyes. No smoking. Wash hands and exposed parts of the body thoroughly after handling. Use only outdoors or in a well-ventilated area. Use personal protective equipment as per Section 8. Observe valid legal regulations on safety and health protection. Ground and bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Take action to prevent static discharges.

#### 7.2. Conditions for safe storage, including any incompatibilities

Store in tightly closed containers in cold, dry and well ventilated areas designated for this purpose. Do not expose to sunlight. Store locked up. Keep container tightly closed. Keep cool.

Storage class 3 - Flammable liquids

#### The specific requirements or rules relating to the substance/mixture

Solvent vapours are heavier than air and accumulate especially near the floor where they may form an explosive mixture with the air.

#### 7.3. Specific end use(s)

not available

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

The mixture contains substances for which occupational exposure limits are set.

#### European Union

#### Commission Directive (EU) 2017/164

Substance name (component)	Type	Value
tetraethyl silicate (CAS: 78-10-4)	OEL 8 hours	44 mg/m <sup>3</sup>
	OEL 8 hours	5 ppm

# SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

## Ceramic PRO BASE

Creation date	30th January 2024	Version	1.0
Revision date			

### 8.2. Exposure controls

Take off contaminated clothing and wash before reuse. Follow the usual measures intended for health protection at work and especially for good ventilation. This can be achieved only by local suction or efficient general ventilation. If exposure limits cannot be observed in this mode, suitable protection of airways must be used. Do not eat, drink and smoke during work. Wash your hands thoroughly with water and soap after work and before breaks for a meal and rest.

#### Eye/face protection

Protective goggles.

#### Skin protection

Hand protection: Protective gloves resistant to the product. When choosing appropriate thickness, material and permeability of the gloves, observe recommendations of their particular manufacturer. Observe other recommendations of the manufacturer. Other protection: protective workwear. Contaminated skin should be washed thoroughly.

#### Respiratory protection

Mask with a filter against organic vapours in a poorly ventilated environment.

#### Thermal hazard

Data not available.

#### Environmental exposure controls

Observe usual measures for protection of the environment, see Section 6.2.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	liquid
Colour	colourless
Odour	data not available
Melting point/freezing point	data not available
Boiling point or initial boiling point and boiling range	>35 °C
Flammability	data not available
Lower and upper explosion limit	data not available
Flash point	20 °C
Auto-ignition temperature	data not available
Decomposition temperature	data not available
pH	8 (undiluted)
Kinematic viscosity	data not available
Solubility in water	data not available
Partition coefficient n-octanol/water (log value)	data not available
Vapour pressure	data not available
propan-2-ol (CAS: 67-63-0)	43 hPa at 20 °C
Density and/or relative density	
Density	0.95 g/cm <sup>3</sup>
propan-2-ol (CAS: 67-63-0)	0.79 g/cm <sup>3</sup>
Relative vapour density	data not available
Particle characteristics	data not available

### 9.2. Other information

not available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

When used in the standard way, there is not any dangerous reaction with other substances.

### 10.2. Chemical stability

The product is stable under normal conditions.

### 10.3. Possibility of hazardous reactions

Unknown.

# SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

## Ceramic PRO BASE

Creation date 30th January 2024  
Revision date Version 1.0

### 10.4. Conditions to avoid

The product is stable and no degradation occurs under normal use. Protect against flames, sparks, overheating and against frost.

### 10.5. Incompatible materials

Protect against strong acids, bases and oxidizing agents.

### 10.6. Hazardous decomposition products

Not developed under normal uses. Dangerous outcomes such as carbon monoxide and carbon dioxide are formed at high temperature and in fire.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Inhalation of solvent vapors above values exceeding exposure limits for working environment may result in acute inhalation poisoning, depending on the level of concentration and exposure time. No toxicological data is available for the mixture.

#### Acute toxicity

Based on the available data, the criteria for classification of the mixture are not met.

Ceramic PRO BASE							
Route of exposure	Parameter	Method	Value	Exposure time	Species	Sex	Value determination
Inhalation (vapor)	ATE		73.33 mg/l				Calculation of value

propan-2-ol							
Route of exposure	Parameter	Method	Value	Exposure time	Species	Sex	Value determination
Inhalation (vapor)	LC <sub>50</sub>	OECD 403	>10000 ppm	6 hours	Rat	F/M	

#### Skin corrosion/irritation

Causes skin irritation. Data for the components of the mixture are not available.

#### Serious eye damage/irritation

Causes serious eye irritation.

propan-2-ol				
Route of exposure	Result	Method	Exposure time	Species
Eye	Serious eye damage	OECD 405		Rabbit

#### Respiratory or skin sensitisation

Data for the mixture are not available. Based on the available data, the criteria for classification of the mixture are not met.

propan-2-ol				
Route of exposure	Result	Exposure time	Species	Sex
	Not sensitizing		Guinea-pig	F/M

# SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

## Ceramic PRO BASE

Creation date 30th January 2024  
Revision date Version 1.0

### Germ cell mutagenicity

Data for the mixture are not available. Based on the available data, the criteria for classification of the mixture are not met.

propan-2-ol				
Result	Exposure time	Specific target organ	Species	Sex
Negative without metabolic activation, Negative with metabolic activation		Ovary	Guinea-pig	F/M

### Carcinogenicity

No data are available for either the mixture or the components. Based on the available data, the criteria for classification of the mixture are not met.

### Reproductive toxicity

No data are available for either the mixture or the components. Based on the available data, the criteria for classification of the mixture are not met.

### Toxicity for specific target organ - single exposure

May cause respiratory irritation. Data for the components of the mixture are not available.

### Toxicity for specific target organ - repeated exposure

Data for the mixture are not available. Based on the available data, the criteria for classification of the mixture are not met.

propan-2-ol					
Route of exposure	Parameter	Value	Result	Species	Sex
Inhalation (vapor)	NOEC	500 ppm		Rat (Rattus norvegicus)	F/M

### Aspiration hazard

May be fatal if swallowed and enters airways. Data for the components of the mixture are not available.

## 11.2. Information on other hazards

The mixture does not contain substances with endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

## SECTION 12: Ecological information

### 12.1. Toxicity

Data for the mixture are not available. Based on the available data, the criteria for classification of the mixture are not met.

#### Acute toxicity

propan-2-ol				
Parameter	Value	Exposure time	Species	Environment
EC <sub>50</sub>	>10000 mg/l	48 hours	Daphnia (Daphnia magna)	
LC <sub>50</sub>	9640 mg/l	96 hours	Fish	Fresh water

### 12.2. Persistence and degradability

No data are available for either the mixture or the components. The mixture is biodegradable.

### 12.3. Bioaccumulative potential

No data are available for either the mixture or the components.

### 12.4. Mobility in soil

# SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

## Ceramic PRO BASE

Creation date 30th January 2024  
Revision date Version 1.0

No data are available for either the mixture or the components.

### 12.5. Results of PBT and vPvB assessment

Product does not contain any substance meeting the criteria for PBT or vPvB in accordance with the Annex XIII of Regulation (EC) No 1907/2006 (REACH) as amended.

### 12.6. Endocrine disrupting properties

The mixture does not contain substances with endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

### 12.7. Other adverse effects

Data not available.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Hazard of environmental contamination; dispose of the waste in accordance with the local and/or national regulations. Proceed in accordance with valid regulations on waste disposal. Any unused product and contaminated packaging should be put in labelled containers for waste collection and submitted for disposal to a person authorised for waste removal (a specialized company) that is entitled for such activity. Do not empty unused product in drainage systems. The product must not be disposed of with municipal waste. Empty containers may be used at waste incinerators to produce energy or deposited in a dump with appropriate classification. Perfectly cleaned containers can be submitted for recycling.

#### Waste management legislation

Directive 2008/98/EC of the European Parliament and of the Council of 19 November 2008 on waste, as amended. Decision 2000/532/EC establishing a list of wastes, as amended.

## SECTION 14: Transport information

### 14.1. UN number or ID number

UN 1993

### 14.2. UN proper shipping name

FLAMMABLE LIQUID, N.O.S. (Silicic acid (H<sub>4</sub>SiO<sub>4</sub>), tetraethyl ester, hydrolyzed; Propan-2-ol)

### 14.3. Transport hazard class(es)

3 Flammable liquids

### 14.4. Packing group

II

### 14.5. Environmental hazards

not relevant

### 14.6. Special precautions for user

Reference in the Sections 4 to 8.

### 14.7. Maritime transport in bulk according to IMO instruments

not relevant

#### Additional information

Hazard identification No.

30

UN number

1993

Classification code

F1

Safety signs

3



Tunnel restriction code

(D/E)

#### Marine transport - IMDG

EmS (emergency plan)

F-E, S-E

MFAG

310



# SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

## Ceramic PRO BASE

Creation date 30th January 2024  
Revision date Version 1.0

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No. 1907/2006 of the European Parliament and of the Council of 18th December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing the European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No. 793/93 and Commission Regulation (EC) No. 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, as amended. REGULATION (EC) No. 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL as amended. REGULATION (EC) No 648/2004 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 31 March 2004 on detergents, as amended. Commission Regulation (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

#### 15.2. Chemical safety assessment

A chemical safety assessment has not been carried out (mixture).

### SECTION 16: Other information

#### A list of standard risk phrases used in the safety data sheet

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.

#### Guidelines for safe handling used in the safety data sheet

P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P280	Wear protective gloves.
P301+P310	IF SWALLOWED: Immediately call a doctor.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P331	Do NOT induce vomiting.
P405	Store locked up.

#### A list of additional standard phrases used in the safety data sheet

EUH066	Repeated exposure may cause skin dryness or cracking.
--------	-------------------------------------------------------

#### Other important information about human health protection

The product must not be - unless specifically approved by the manufacturer/importer - used for purposes other than as per the Section 1. The user is responsible for adherence to all related health protection regulations.

#### Key to abbreviations and acronyms used in the safety data sheet

ADR	European agreement concerning the international carriage of dangerous goods by road
BCF	Bioconcentration Factor
CAS	Chemical Abstracts Service
CLP	Regulation (EC) No 1272/2008 on classification, labelling and packaging of substance and mixtures
EC	Identification code for each substance listed in EINECS
EC <sub>50</sub>	Concentration of a substance when it is affected 50% of the population
EINECS	European Inventory of Existing Commercial Chemical Substances
EmS	Emergency plan
EU	European Union
EuPCS	European Product Categorisation System
IATA	International Air Transport Association
IBC	International Code For The Construction And Equipment of Ships Carrying Dangerous Chemicals
ICAO	International Civil Aviation Organization

# SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

## Ceramic PRO BASE

Creation date	30th January 2024	Version	1.0
Revision date			

IMDG	International Maritime Dangerous Goods
IMO	International Maritime Organization
INCI	International Nomenclature of Cosmetic Ingredients
ISO	International Organization for Standardization
IUPAC	International Union of Pure and Applied Chemistry
LC <sub>50</sub>	Lethal concentration of a substance in which it can be expected death of 50% of the population
log K <sub>ow</sub>	Octanol-water partition coefficient
NOEC	No observed effect concentration
OEL	Occupational Exposure Limits
PBT	Persistent, Bioaccumulative and Toxic
ppm	Parts per million
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Agreement on the transport of dangerous goods by rail
UN	Four-figure identification number of the substance or article taken from the UN Model Regulations
UVCB	Substances of unknown or variable composition, complex reaction products or biological materials
VOC	Volatile organic compounds
vPvB	Very Persistent and very Bioaccumulative

Acute Tox.	Acute toxicity
Asp. Tox.	Aspiration hazard
Eye Irrit.	Eye irritation
Flam. Liq.	Flammable liquid
Skin Irrit.	Skin irritation
STOT SE	Specific target organ toxicity - single exposure

### Training guidelines

Inform the personnel about the recommended ways of use, mandatory protective equipment, first aid and prohibited ways of handling the product.

### Recommended restrictions of use

not available

### Information about data sources used to compile the Safety Data Sheet

REGULATION (EC) No. 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL (REACH) as amended. REGULATION (EC) No. 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL as amended. Data from the manufacturer of the substance / mixture, if available - information from registration dossiers.

### More information

Classification procedure - calculation method.

### Statement

The safety data sheet provides information aimed at ensuring safety and health protection at work and environmental protection. The provided information corresponds to the current status of knowledge and experience and complies with valid legal regulations. The information should not be understood as guaranteeing the suitability and usability of the product for a particular application.