according to Commission Regulation (EU) 2020/878 as amended

EXTERIOR PLASTIC TIRE DRESSING

Creation date 31st January 2024

Revision date Version 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier EXTERIOR PLASTIC TIRE DRESSING

Substance / mixture mixture

UFI 8W10-20VN-S00Y-DW66

1.2. Relevant identified uses of the substance or mixture and uses advised against

Mixture's intended use

Main intended use

PC-CLN-17.1 Exterior cleaning products - all vehicle types

Secondary uses

PC-CLN-17.2 Exterior care products - all vehicle types

Mixture uses advised against

The product should not be used in ways other than those referred in Section 1.

1.3. Details of the supplier of the safety data sheet

Supplier

Name or trade name Magis Agata Nizio

Address Mickiewicza 11, Dębno, 74-400

Poland

 VAT Reg No
 PL5970003622

 Phone
 +48451013350

 E-mail
 ggg@gmail.com

Competent person responsible for the safety data sheet

Name Magis Agata Nizio E-mail ggg@gmail.com

1.4. Emergency telephone number

European emergency number: 112

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification of the mixture in accordance with Regulation (EC) No 1272/2008

The mixture is classified as dangerous.

Flam. Liq. 3, H226

Most serious adverse physico-chemical effects

Flammable liquid and vapour.

Most serious adverse effects on human health and the environment

Causes serious eye irritation.

2.2. Label elements

Hazard pictogram



Signal word

Warning

Hazard statements

H226 Flammable liquid and vapour.

Precautionary statements

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P403+P235 Store in a well-ventilated place. Keep cool.

according to Commission Regulation (EU) 2020/878 as amended

EXTERIOR PLASTIC TIRE DRESSING

Creation date 31st January 2024

Revision date Version 1.0

P501 Dispose of contents/container to by handing over to the person authorized to

dispose of waste or by returning to the supplier.

Supplemental information

EUH208 Contains reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-

isothiazol-3-one (3:1). May produce an allergic reaction.

Composition according to (EC) No 648/2004, as amended: perfumes, METHYLCHLOROISOTHIAZOLINONE, METHYLISOTHIAZOLINONE

2.3. Other hazards

The mixture does not contain substances with endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605. Mixture does not contain any substance meet the criteria for PBT or vPvB in accordance with Annex XIII of Regulation (EC) No. 1907/2006 (REACH) as amended.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Mixture contains these hazardous substances and substances with the highest permissible concentration in the working environment

Identification numbers	Substance name	Content in % weight	Classification according to Regulation (EC) No 1272/2008	Note
Index: 603-117-00-0 CAS: 67-63-0 EC: 200-661-7 Registration number: 01-2119457558-25	propan-2-ol	<10	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336	
Index: 613-167-00-5 CAS: 55965-84-9	reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	<0,0015	Acute Tox. 3, H301 Acute Tox. 2, H310+H330 Skin Corr. 1C, H314 Skin Sens. 1A, H317 Eye Dam. 1, H318 Aquatic Acute 1, H400 (M=100) Aquatic Chronic 1, H410 (M=100) EUH071 Specific concentration limit: Eye Irrit. 2, H319: $0.06 \% \le C < 0.6 \%$ Skin Sens. 1A, H317: $C \ge 0.0015 \%$ Skin Irrit. 2, H315: $0.06 \% \le C < 0.6 \%$ Skin Corr. 1C, H314: $C \ge 0.6 \%$ Eye Dam. 1, H318: $C \ge 0.6 \%$	1

Notes

Note B: Some substances (acids, bases, etc.) are placed on the market in aqueous solutions at various concentrations and, therefore, these solutions require different classification and labelling since the hazards vary at different concentrations. In Part 3 entries with Note B have a general designation of the following type: 'nitric acid ... %'. In this case the supplier must state the percentage concentration of the solution on the label. Unless otherwise stated, it is assumed that the percentage concentration is calculated on a weight/weight basis.

Full text of all classifications and hazard statements is given in the section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Take care of your own safety. If any health problems are manifested or if in doubt, inform a doctor and show him information from this safety data sheet. If unconscious, put the person in the stabilized (recovery) position on his side with his head slightly bent backwards and make sure that airways are free; never induce vomiting. If the person vomits by himself, make sure that the vomit is not inhaled. In life threatening conditions first of all provide resuscitation of the affected person and ensure medical assistance. Respiratory arrest - provide artificial respiration immediately. Cardiac arrest - provide indirect cardiac massage immediately.

according to Commission Regulation (EU) 2020/878 as amended

EXTERIOR PLASTIC TIRE DRESSING

Creation date 31st January 2024

Revision date Version 1.0

If inhaled

Terminate the exposure immediately; move the affected person to fresh air. Protect the person against growing cold. Provide medical treatment if irritation, dyspnoea or other symptoms persist.

If on skin

Remove contaminated clothes. Wash the affected area with plenty of water, lukewarm if possible. Soap, soap solution or shampoo should be used if there is no skin injury. Provide medical treatment if skin irritation persists. Rinse skin with water or shower.

If in eyes

Rinse eyes immediately with a flow of running water, open the eyelids (also using force if needed); remove contact lenses immediately if worn by the affected person. Rinsing should continue at least for 10 minutes. Provide medical treatment, specialized if possible.

If swallowed

Rinse out the mouth with water and provide 2-5 dL of water. Provide medical treatment if the person has any health problems.

4.2. Most important symptoms and effects, both acute and delayed

If inhaled

Not expected.

If on skin

Not expected.

If in eyes

Causes serious eye irritation.

If swallowed

Irritation, nausea.

4.3. Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Alcohol-resistant foam, carbon dioxide, powder, water spray jet, water mist.

Unsuitable extinguishing media

Water - full jet.

5.2. Special hazards arising from the substance or mixture

In the event of fire, carbon monoxide, carbon dioxide and other toxic gases may arise. Inhalation of hazardous degradation (pyrolysis) products may cause serious health damage.

5.3. Advice for firefighters

Self-Contained Breathing Apparatus (SCBA) with a chemical protection suit only where personal (close) contact is likely. Use a self-contained breathing apparatus and full-body protective clothing. Closed containers with the product near the fire should be cooled with water. Do not allow run-off of contaminated fire extinguishing material to enter drains or surface and ground water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Provide sufficient ventilation. Flammable liquid and vapour. Remove all ignition sources. Use personal protective equipment for work. Follow the instructions in the Sections 7 and 8. Prevent contact with skin and eyes.

6.2. Environmental precautions

Prevent contamination of the soil and entering surface or ground water.

6.3. Methods and material for containment and cleaning up

Spilled product should be covered with suitable (non-flammable) absorbing material (sand, diatomaceous earth, earth and other suitable absorption materials); to be contained in well closed containers and removed as per the Section 13. In the event of leakage of the substantial amount of the product, inform fire brigade and other competent bodies. After removal of the product, wash the contaminated site with plenty of water. Do not use solvents.

6.4. Reference to other sections

See the Section 7, 8 and 13.

according to Commission Regulation (EU) 2020/878 as amended

EXTERIOR PLASTIC TIRE DRESSING

Creation date 31st January 2024

Revision date Version 1.0

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Prevent formation of gases and vapours in flammable or explosive concentrations and concentrations exceeding the occupational exposure limits. The product should be used only in the areas where it is not in contact with open fire and other ignition sources. Use non-sparking tools. Use of antistatic clothes and footwear is recommended. Prevent contact with skin and eyes. No smoking. Wash hands and exposed parts of the body thoroughly after handling. Use personal protective equipment as per Section 8. Observe valid legal regulations on safety and health protection. Ground and bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Take action to prevent static discharges.

7.2. Conditions for safe storage, including any incompatibilities

Store in tightly closed containers in cold, dry and well ventilated areas designated for this purpose. Do not expose to sunlight. Keep container tightly closed. Keep cool.

Storage class 3 - Flammable liquids Storage temperature min 15 °C, max 25 °C

The specific requirements or rules relating to the substance/mixture

Solvent vapours are heavier than air and accumulate especially near the floor where they may form an explosive mixture with the air.

7.3. Specific end use(s)

not available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

The mixture contains substances for which occupational exposure limits are set.

8.2. Exposure controls

Do not eat, drink and smoke during work. Wash your hands thoroughly with water and soap after work and before breaks for a meal and rest.

Eye/face protection

Protective goggles.

Skin protection

Hand protection: Protective gloves resistant to the product. Contaminated skin should be washed thoroughly.

Respiratory protection

Halfmask with a filter against organic vapours or a self-contained breathing apparatus as appropriate if exposure limit values of substances are exceeded or in a poorly ventilated environment.

82 °C

Thermal hazard

Data not available.

Environmental exposure controls

Observe usual measures for protection of the environment, see Section 6.2.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state liquid
Colour data not available
Odour data not available
Melting point/freezing point data not available

Boiling point or initial boiling point and boiling range

Flammability data not available

Lower and upper explosion limit

bottom 2 % upper 12 % Flash point 26.5 °C Auto-ignition temperature 425 °C

Decomposition temperature data not available pH 8.1 (undiluted)
Kinematic viscosity >21 mm²/s at 40 °C
Solubility in water data not available

according to Commission Regulation (EU) 2020/878 as amended

EXTERIOR PLASTIC TIRE DRESSING

Creation date 31st January 2024

1.0 Revision date Version

Partition coefficient n-octanol/water (log value) data not available

Vapour pressure 48 hPa

propan-2-ol (CAS: 67-63-0) 43 hPa at 20 °C

Density and/or relative density

Density 0.97 g/cm³ propan-2-ol (CAS: 67-63-0) 0.79 g/cm³

Relative vapour density data not available Particle characteristics data not available

9.2. Other information

not available

SECTION 10: Stability and reactivity

10.1. Reactivity

not available

10.2. Chemical stability

The product is stable under normal conditions.

10.3. Possibility of hazardous reactions

Unknown.

10.4. Conditions to avoid

The product is stable and no degradation occurs under normal use. Protect against flames, sparks, overheating and against frost.

10.5. Incompatible materials

Protect against strong acids, bases and oxidizing agents.

10.6. Hazardous decomposition products

Not developed under normal uses. Dangerous outcomes such as carbon monoxide and carbon dioxide are formed at high temperature and in fire.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Inhalation of solvent vapors above values exceeding exposure limits for working environment may result in acute inhalation poisoning, depending on the level of concentration and exposure time. No toxicological data is available for the mixture.

Acute toxicity

Based on the available data, the criteria for classification of the mixture are not met.

EXTERIOR PL	EXTERIOR PLASTIC TIRE DRESSING									
Route of exposure	Parameter	Method	Value	Exposure time	Species	Sex	Value determination			
Oral	ATE		6711000 mg/kg				Calculation of value			
Dermal	ATE		3356000 mg/kg				Calculation of value			
Inhalation (vapor)	ATE		33560 mg/l				Calculation of value			

propan-2-ol								
Route of exposure	Parameter	Method	Value	Exposure time	Species	Sex	Value determination	
Inhalation (vapor)	LC50	OECD 403	>10000 ppm	6 hours	Rat	F/M		

Skin corrosion/irritation

No data are available for either the mixture or the components. Based on the available data, the criteria for classification of the mixture are not met.

according to Commission Regulation (EU) 2020/878 as amended

EXTERIOR PLASTIC TIRE DRESSING

Creation date 31st January 2024

Revision date Version 1.0

Serious eye damage/irritation

Causes serious eye irritation.

propan-2-ol						
Route of exposure	Result	Method	Exposure time	Species		
Eye	Serious eye damage	OECD 405		Rabbit		

Respiratory or skin sensitisation

Data for the mixture are not available. Based on the available data, the criteria for classification of the mixture are not met.

propan-2-ol						
Route of exposure	Result	Exposure time	Species	Sex		
	Not sensitizing		Guinea-pig	F/M		

Germ cell mutagenicity

Data for the mixture are not available. Based on the available data, the criteria for classification of the mixture are not met.

propan-2-ol							
Result	Exposure time	Specific target organ	Species	Sex			
Negative without metabolic activation, Negative with metabolic activation		Ovary	Guinea-pig	F/M			

Carcinogenicity

No data are available for either the mixture or the components. Based on the available data, the criteria for classification of the mixture are not met.

Reproductive toxicity

No data are available for either the mixture or the components. Based on the available data, the criteria for classification of the mixture are not met.

Toxicity for specific target organ - single exposure

No data are available for either the mixture or the components. Based on the available data, the criteria for classification of the mixture are not met.

Toxicity for specific target organ - repeated exposure

Data for the mixture are not available. Based on the available data, the criteria for classification of the mixture are not met.

propan-2-ol							
Route of exposure	Parameter	Value	Result	Species	Sex		
Inhalation (vapor)	NOEC	500 ppm		Rat (Rattus norvegicus)	F/M		

Aspiration hazard

No data are available for either the mixture or the components. Based on the available data, the criteria for classification of the mixture are not met.

11.2. Information on other hazards

The mixture does not contain substances with endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

according to Commission Regulation (EU) 2020/878 as amended

EXTERIOR PLASTIC TIRE DRESSING

Creation date 31st January 2024

Revision date Version 1.0

SECTION 12: Ecological information

12.1. Toxicity

Data for the mixture are not available. Based on the available data, the criteria for classification of the mixture are not met.

Acute toxicity

propan-2-ol							
Parameter	Value	Exposure time	Species	Environment			
EC50	>10000 mg/l	48 hours	Daphnia (Daphnia magna)				
LC50	9640 mg/l	96 hours	Fish	Fresh water			

12.2. Persistence and degradability

No data are available for either the mixture or the components.

12.3. Bioaccumulative potential

No data are available for either the mixture or the components.

12.4. Mobility in soil

No data are available for either the mixture or the components.

12.5. Results of PBT and vPvB assessment

Product does not contain any substance meeting the criteria for PBT or vPvB in accordance with the Annex XIII of Regulation (EC) No 1907/2006 (REACH) as amended.

12.6. Endocrine disrupting properties

The mixture does not contain substances with endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

12.7. Other adverse effects

Data not available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Hazard of environmental contamination; dispose of the waste in accordance with the local and/or national regulations. Proceed in accordance with valid regulations on waste disposal. Any unused product and contaminated packaging should be put in labelled containers for waste collection and submitted for disposal to a person authorised for waste removal (a specialized company) that is entitled for such activity. Do not empty unused product in drainage systems. The product must not be disposed of with municipal waste. Empty containers may be used at waste incinerators to produce energy or deposited in a dump with appropriate classification. Perfectly cleaned containers can be submitted for recycling.

Waste management legislation

Directive 2008/98/EC of the European Parliament and of the Council of 19 November 2008 on waste, as amended. Decision 2000/532/EC establishing a list of wastes, as amended.

SECTION 14: Transport information

14.1. UN number or ID number

UN 1993

14.2. UN proper shipping name

FLAMMABLE LIQUID, N.O.S. ((isopropanol)

14.3. Transport hazard class(es)

3 Flammable liquids

14.4. Packing group

III

14.5. Environmental hazards

not relevant

14.6. Special precautions for user

Reference in the Sections 4 to 8.

14.7. Maritime transport in bulk according to IMO instruments

not relevant

according to Commission Regulation (EU) 2020/878 as amended

EXTERIOR PLASTIC TIRE DRESSING

Creation date 31st January 2024

Revision date Version 1.0

Additional information

Hazard identification No.

UN number Classification code Safety signs 30 1993

F1 3



Tunnel restriction code (D/E)

Marine transport - IMDG

EmS (emergency plan) F-E, S-E MFAG 310

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No. 1907/2006 of the European Parliament and of the Council of 18th December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing the European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EC) No. 793/93 and Commission Regulation (EC) No. 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, as amended. REGULATION (EC) No. 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL as amended. REGULATION (EC) No 648/2004 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 31 March 2004 on detergents, as amended. Commission Regulation (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

15.2. Chemical safety assessment

not available

SECTION 16: Other information

Δ	list of	standard	risk	nhrases	used in	the	safety	data	sheet
_	HISL OI	Stallualu	1136	viii ases	useu III	uic	Saict	uata	SHEEL

H225 Highly flammable liquid and vapour. H226 Flammable liquid and vapour.

H301 Toxic if swallowed.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.
 H318 Causes serious eye damage.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H310+H330 Fatal in contact with skin or if inhaled.

Guidelines for safe handling used in the safety data sheet

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container to by handing over to the person authorized to

dispose of waste or by returning to the supplier.

A list of additional standard phrases used in the safety data sheet

EUH208 Contains reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-

isothiazol-3-one (3:1). May produce an allergic reaction.

according to Commission Regulation (EU) 2020/878 as amended

EXTERIOR PLASTIC TIRE DRESSING

Creation date 31st January 2024

Revision date Version 1.0

EUH071 Corrosive to the respiratory tract.

Other important information about human health protection

The product must not be - unless specifically approved by the manufacturer/importer - used for purposes other than

as per the Section 1. The user is responsible for adherence to all related health protection regulations.

Key to abbreviations and acronyms used in the safety data sheet

ADR European agreement concerning the international carriage of dangerous goods by

road

BCF Bioconcentration Factor
CAS Chemical Abstracts Service

CLP Regulation (EC) No 1272/2008 on classification, labelling and packaging of

substance and mixtures

EC Identification code for each substance listed in EINECS

EC50 Concentration of a substance when it is affected 50% of the population EINECS European Inventory of Existing Commercial Chemical Substances

EmS Emergency plan EU European Union

EuPCS European Product Categorisation System
IATA International Air Transport Association

IBC International Code For The Construction And Equipment of Ships Carrying

Dangerous Chemicals

ICAO International Civil Aviation Organization
IMDG International Maritime Dangerous Goods
IMO International Maritime Organization

INCI International Nomenclature of Cosmetic Ingredients
ISO International Organization for Standardization
IUPAC International Union of Pure and Applied Chemistry

LC50 Lethal concentration of a substance in which it can be expected death of 50% of the

population

log KowOctanol-water partition coefficientNOECNo observed effect concentrationOELOccupational Exposure Limits

PBT Persistent, Bioaccumulative and Toxic

ppm Parts per million

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals

RID Agreement on the transport of dangerous goods by rail

UN Four-figure identification number of the substance or article taken from the UN

Model Regulations

UVCB Substances of unknown or variable composition, complex reaction products or

biological materials

VOC Volatile organic compounds

vPvB Very Persistent and very Bioaccumulative

Acute Tox. Acute toxicity

Aquatic Acute Hazardous to the aquatic environment

Aquatic Chronic Hazardous to the aquatic environment (chronic)

Eye Dam. Serious eye damage Flam. Liq. Flammable liquid Skin Corr. Skin corrosion Skin Sens. Skin sensitization

STOT SE Specific target organ toxicity - single exposure

Training guidelines

Inform the personnel about the recommended ways of use, mandatory protective equipment, first aid and prohibited ways of handling the product.

Recommended restrictions of use

not available

Information about data sources used to compile the Safety Data Sheet

according to Commission Regulation (EU) 2020/878 as amended

EXTERIOR PLASTIC TIRE DRESSING

Creation date 31st January 2024

Revision date Version 1.0

REGULATION (EC) No. 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL (REACH) as amended. REGULATION (EC) No. 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL as amended. Data from the manufacturer of the substance / mixture, if available - information from registration dossiers.

More information

Classification procedure - calculation method.

Statement

The safety data sheet provides information aimed at ensuring safety and health protection at work and environmental protection. The provided information corresponds to the current status of knowledge and experience and complies with valid legal regulations. The information should not be understood as guaranteeing the suitability and usability of the product for a particular application.